





LATUS L CERAMIC  
Blanco

LATUS L CERAMIC  
Negro

LATUS L CERAMIC  
Nieve

LATUS L PL CERAMIC

PL = Top connection



LATUS R CERAMIC  
Blanco

LATUS R CERAMIC  
Negro

LATUS R CERAMIC  
Nieve

LATUS R PL CERAMIC

**PRODUCT INFORMATION:**

<b>Thermal energy:</b>	56,4 kWh,	<b>PL: 56,4 kWh</b>
<b>Energy efficiency:</b>	84 %,	<b>PL: 84 %</b>
<b>CO%:</b>	0,09 %,	<b>PL: 0,09 %</b>
<b>Heat storage capacity:</b>		
	100 % after 7,3 hours,	<b>PL: after 7,3 hours</b>
	50 % after 27,4 hours,	<b>PL: after 27,4 hours</b>
	25 % after 50,2 hours,	<b>PL: after 50,2 hours</b>

**PRODUCT NUMBERS:**

Product	Product number	Weight kg	Height mm
LATUS L CERAMIC	2TLLC	1940	1543
LATUS R CERAMIC	2TLRC	1940	1543
LATUS L PL CERAMIC	2TLLPC	1950	1543
LATUS R PL CERAMIC	2TLRPC	1950	1543

**NEEDED FOR ASSEMBLY:**

\* Mortar 2 x 25 kg (not included in NunnaUuni delivery)

## PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Latus R/L Ceramic	-	-	33	16	-	213	-12	21	160	285
Latus R/L PL Ceramic	-	-	33	16	-	213	-12	21	180	285

## FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Latus R/L Ceramic	-	x	x	160-210	150-180	210	1410	370	-	920006	35 - 50
Latus R/L PL Ceramic	-	-	-	180	-	-	-	370	-	920006	35 - 50

## SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Latus R/L Ceramic	50	150	200	1000
Latus R/L PL Ceramic	50	150	200	1000

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

### NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

**Country- and region-specific regulations must be adhered to when installing the fireplace**

