

LATUS TUNNEL CERAMIC

PRODUCT INFORMATION:

Thermal energy:	59,2 kWh,	PL: 59,2 kWh
Energy efficiency:	85 %,	PL: 85 %
CO%:	0,09 %,	PL: 0,09 %
Heat storage capacity:		
	100 % after 7,2 hours,	PL: after 7,2 hours
	50 % after 27,2 hours,	PL: after 27,2 hours
	25 % after 49,8 hours,	PL: after 49,8 hours





PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
LATUS TUNNEL L CERAMIC	2TLTLC	1940	1543
LATUS TUNNEL R CERAMIC	2TLTRC	1940	1543
LATUS TUNNEL L PL CERAMIC	2TLT LPC	1950	1543
LATUS TUNNEL R PL CERAMIC	2TLTRPC	1950	1543

NEEDED FOR ASSEMBLY:

* Mortar 2 x 25 kg (not included in NunnaUuni delivery)

PL = Top connection







LATUS TUNNEL L CERAMIC
Blanco

LATUS TUNNEL L CERAMIC
Negro

LATUS TUNNEL L CERAMIC
Nieve

LATUS TUNNEL L PL CERAMIC



LATUS TUNNEL R CERAMIC
Blanco

LATUS TUNNEL R CERAMIC
Negro

LATUS TUNNEL R CERAMIC
Nieve

LATUS TUNNEL R PL CERAMIC

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES ⁽¹⁾				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Latus Tunnel R/L Ceramic	-	-	33	16	-	209	-12	19	160	321
Latus Tunnel R/L PL Ceramic	-	-	33	16	-	209	-12	19	180	321

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Latus Tunnel R/L Ceramic	-	x	x	160-210	150-180	210	1410	370	-	920006	35 - 50
Latus Tunnel R/L PL Ceramic	-	-	-	180	-	-	-	370	-	920006	35 - 50

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Latus Tunnel R/L Ceramic	1000	150	200	1000
Latus Tunnel R/L PL Ceramic	1000	150	200	1000

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

Country- and region-specific regulations must be adhered to when installing the fireplace

